

GCL- M10/72GDF



535-555 W

**Bifacial Dual Glass
Monocrystalline Module**

555W

Maximum Power Output

21.5%

Maximum Module Efficiency

0~+5W

Power Output Guarantee



GCL Delivers Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard: ISO 9001, ISO 14001 and ISO 45001
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068-2-68)
- Long term reliability tests
- 2x100% EL inspection ensuring defect-free modules



Ideal choice for large scale ground installation



High conversion efficiency due to top quality wafers and advanced cell technology



Additional safety, Fire class A certified



Withstand up to 1500V system voltage effectively reduce BOS cost




Selected encapsulating material and stringent production process control ensure the product is highly PID resistant and snail trails free



Sand blowing test, salt mist test and ammonia test passed to endure harsh environments

Linear Performance Warranty



* Please refer to GCL standard warranty for details

Additional Insurance Backed by Swiss RE

* Please refer to GCL for details



Electrical Specification (STC*)

Maximum Power	P _{max} (W)	535	540	545	550	555
Maximum Power Voltage	V _{mp} (V)	41.22	41.45	41.70	41.93	42.18
Maximum Power Current	I _{mp} (A)	12.98	13.03	13.07	13.12	13.16
Open Circuit Voltage	V _{oc} (V)	48.96	49.24	49.52	49.80	50.08
Short Circuit Current	I _{sc} (A)	13.73	13.78	13.83	13.88	13.93
Module Efficiency	(%)	20.7	20.9	21.1	21.3	21.5
Power Output Tolerance	(W)			0~+5		

* Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5

Electrical Specification (NMOT*)

Maximum Power	P _{max} (W)	404.8	408.6	412.4	416.2	420.0
Maximum Power Voltage	V _{mp} (V)	38.23	38.45	38.67	38.90	39.12
Maximum Power Current	I _{mp} (A)	10.58	10.62	10.66	10.70	10.74
Open Circuit Voltage	V _{oc} (V)	46.21	46.48	46.74	47.01	47.28
Short Circuit Current	I _{sc} (A)	11.00	11.04	11.08	11.12	11.16

* Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Electrical characteristics with different power bin (reference to 10% Irradiance ratio)

Maximum Power	P _{max} (W)	572.5	577.8	583.2	588.5	593.9
Maximum Power Voltage	V _{mp} (V)	41.22	41.45	41.70	41.93	42.18
Maximum Power Current	I _{mp} (A)	13.89	13.94	13.98	14.04	14.08
Open Circuit Voltage	V _{oc} (V)	48.96	49.24	49.52	49.80	50.08
Short Circuit Current	I _{sc} (A)	14.69	14.75	14.80	14.85	14.91

Irradiance ratio (rear/front) 10%

Mechanical Data

Number of Cells	144 Cells (6×24)
Dimensions of Module L*W*H (mm)	2278×1134×30 mm (89.69×44.65×1.18 inches)
Weight (kg)	32.7 kg
Front Side Glass	2.0mm (0.08 inches), Anti-Reflection Coating
Back Side Glass	2.0mm (0.08 inches), Heat Strengthened Glass
Frame	Silver, anodized aluminium alloy
J-Box	IP68 Rated
Cable	4.0mm ² , Portrait: +400/-200mm length can be customized
Number of diodes	3
Wind/ Snow Load	2400Pa/ 5400Pa*
Connector	MC Compatible
Bifaciality	70±5%

* For more details please check the installation manual of GCLSI

Temperature Ratings

Nominal Module Operating Temperature(NMOT)	45±2°C
Temperature Coefficient of I _{sc}	+0.05%/°C
Temperature Coefficient of V _{oc}	-0.28%/°C
Temperature Coefficient of P _{MAX}	-0.35%/°C

Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	30A


Optional

Connector: Original MC4


Packaging Configuration

Module per box	36 pieces
Module per 40' container	720 pieces


Module Dimension




Back View



I-V Curve at Different Temperature (555W)



I-V/P-V Curve at Different Irradiation (555W)



CAUTION: READ INSTALLATION MANUAL BEFORE USING THE PRODUCT

Contact Us for More Information

website: www.gclsi.com email: gclsisales@gclsi.com

